

Response to Office Action of 10/3/2003  
Appl. Ser. No. 09/945,385

### Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

#### Listing of Claims:

1. (Currently Amended) Method for nozzle-injection of gas into molten glass, characterized ~~through the following features comprising:~~
  - 1.1 ~~the introducing a gas stream is introduced into the a~~ molten mass in a temporally pulsed, throughput;
  - 1.2 ~~interrupting the gas stream is interrupted between two sequential pulses;~~
  - 1.3 ~~wherein the duration of a the pulses~~ amounts to less than 1 s.
2. (Currently Amended) Method according to claim 1, ~~characterized by the fact that wherein~~ the duration of ~~the a~~ pulses amounts to less than 100 ms.
3. (Currently Amended) Method according to claim 1, ~~characterized by the fact that wherein~~ the duration of ~~the a~~ pulses amounts to less than 50 ms.
4. (Currently Amended) Method according to claim 1, ~~characterized by the fact that wherein~~ following the pulse the pressure falloff of a pulse falls from a maximum value to null takes place within a time span of less than 100 ms.
5. (Currently Amended) Method according to claim 1, ~~characterized by the fact that wherein~~ following the pulse the pressure falloff of a pulse falls from a maximum value to null takes place within a time span of less than 50 ms.
6. (Currently Amended) Method according to claim 1, ~~characterized by the fact that wherein~~ ~~at the~~ temporal interval between two sequential pulses amounts to at least 1 s.

Response to Office Action of 10/3/2003  
Appl. Ser. No. 09/945,385

7. (Currently Amended) Method according to claim 1, ~~characterized by the fact that wherein~~  
~~at~~ the temporal interval between two sequential pulses amounts to at least 10 s.
8. (Currently Amended) Method according to claim 1, ~~characterized through the following~~  
~~features~~ further comprising the step of:
- 8.1 depleting the molten mass ~~is freed of~~ foreign gases through flushing with O<sub>2</sub> gas;
- 8.2 wherein the introduced pulsing of the gas stream produces bubbles ~~are given~~  
having a high surface-area/volume ratio through impressed pressure profiles, in order to  
minimize the ~~bubbling gas amount~~ bubble volume and to maximize the expelling of  
foreign gas.